



Kit Includes:

- A** WalkAbout II™ Display (WM-4) with Chest Harness (WCH)
- B** Sunshade (SS-WA)
- C** D-Cell Battery Pack (D-BAT)
- D** Self-Illuminating, Low Light, Color Camera (LLC-1.4)
- E** Spare Rechargeable Battery (BAT-2)
- F** Battery Charger (WBC)
- G** 2-Foot Baton Extension Pole (B-FNS)
- H** 25-Foot Camera Cable (VPC-25)
- I** Carrying Case (W-CASE)

Note: Also available with sling configuration (Part # WS-BW) →





DELUXE BATON SYSTEM SPECIFICATIONS

WA-BW¹

WalkAbout II Monitor Specifications

Size:	6.4"W x 4.5"H x 2.2"D (LCD); 4.8"L x 3.4"W x 2.8"H (Base)	Weight:	3.75lbs (with battery)
Construction:	Aluminum case encapsulated in rubber for shock resistance and weatherproofing	Operating temperature range:	-20C to 70C
Display size:	5" diagonal	Resolution:	960 dots x 234 lines
Video format:	Auto switches between NTSC (American) or PAL (European) format		
Batteries:	Internal NiMH, 7.2V, 2.7AH	Discharge time:	2hrs - Camera LEDS off & LCD on
Charger:	NiMH charger. Operates on 12VDC from either power supply or vehicle adapter.	Charge time:	2hrs if fully discharged
LCD Controls:	Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down	Base Controls and indicators:	Main On/OFF push button switch; Camera LED intensity control LED Indicators: PWR ON, LOW BAT, CAM LED
Connections:	1) Camera (pole) receptacle, 2) A/V output receptacle, 3) External DC input receptacle, 7.2-12VDC @ 15W max	Mounting options:	Belt clip onto vest/belt or Chest Harness (supplied)

Camera Specifications

Model:	LLC-1.4
Construction:	Submersible enclosure with hard-coated polycarbonate window
Size / weight:	1.4" dia x 2.8" long / .2 lbs
Features:	6 Bright white LED illuminated color camera, 400 lines, .03 lux, 6.0mm lens, 53° FOV

Baton Specifications

Model:	B-FNS
Pole Construction:	Single section fiberglass pole with foam grip
Articulation:	1 ft flexible gooseneck can be flexed to any position
Collapsed length:	1 ft 4 in folded
Extended length:	2 ft
Weight:	lbs

Accessories

Model:	VPC-25	D-BAT	BAT-2
Description:	25 ft submersible camera cable	8 "D" cell battery pack in belt pack (batteries not included)	Spare NiMH battery pack

Case Specifications

Model:	W-CASE
Construction:	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size:	21" x 16" x 8"
Weight loaded:	18 lbs

RECOMMENDED OPTIONS

D-BAT	Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.
Telescoping Pole	Extend reach with either an articulating/telescoping pole or telescoping pole. Many sizes and models available.

Note 1:	Add a "-P" to the end of the system part number to specify a PAL (European TV standard) system (WA-BW-P). Change the system part number prefix "WA-" to "WS-" to specify the WalkAbout Sling (WSH) in place of the Chest Harness (WCH).
----------------	--