

**WALKABOUT POLE SYSTEM**  
PART # WA-SPW11



**E** (comes with S9 soft carry case not shown)

Kit Includes:

- A** WalkAbout II™ Display (WM-4) and Chest Harness (WCH)
- B** Sunshade (SS-WA)
- C** Self-Illuminating, Low Light, Color Camera (WPC-1.2)
- D** Battery Charger (WBC)
- E** 11-Foot Telescoping Extension Pole (T-FNS-11)
- F** Carrying Case (W-CASE)

**Note:** Also available with sling configuration (Part # WS-SPW11) ⇒





# POLE SYSTEM SPECIFICATIONS

## WA-SPW11<sup>1</sup>

### WalkAbout II Monitor Specifications

<b>Size:</b>	6.4"W x 4.5"H x 2.2"D (LCD); 4.8"L x 3.4"W x 2.8"H (Base)	<b>Weight:</b>	3.75lbs (with battery)
<b>Construction:</b>	Aluminum case encapsulated in rubber for shock resistance and weatherproofing	<b>Operating temperature range:</b>	-20C to 70C
<b>Display size:</b>	5" diagonal	<b>Resolution:</b>	960 dots x 234 lines
<b>Video format:</b>	Auto switches between NTSC (American) or PAL (European) format		
<b>Batteries:</b>	Internal NiMH, 7.2V, 2.7AH	<b>Discharge time:</b>	2hrs - Camera LEDS off & LCD on
<b>Charger:</b>	NiMH charger. Operates on 12VDC from either power supply or vehicle adapter.	<b>Charge time:</b>	2hrs if fully discharged
<b>LCD Controls:</b>	Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down	<b>Base Controls and indicators:</b>	Main On/OFF push button switch; Camera LED intensity control LED Indicators: PWR ON, LOW BAT, CAM LED
<b>Connections:</b>	1) Camera (pole) receptacle, 2) A/V output receptacle, 3) External DC input receptacle, 7.2-12VDC @ 15W max	<b>Mounting options:</b>	Belt clip onto vest/belt or Chest Harness (supplied)

### Camera Specifications

<b>Model:</b>	<b>WPC-1.2</b>
<b>Construction:</b>	Submersible enclosure with hard-coated polycarbonate window
<b>Size / weight:</b>	1.2" dia x 3.5" long / .2 lbs
<b>Features:</b>	6 Bright white LED illuminated color camera, 400 lines, .03 lux, 6.0 mm lens, 53° FOV

### Pole Specifications

<b>Model:</b>	<b>T-FNS-11</b>
<b>Pole Construction:</b>	3 section telescoping fiberglass pole with foam grip
<b>Collars:</b>	Rugged, break-proof, easy grip, twist collars for each pole section
<b>Articulation:</b>	1 ft flexible gooseneck can be flexed to any position
<b>Collapsed length:</b>	4 ft collapsed and folded
<b>Extended length:</b>	11 ft
<b>Weight:</b>	4 lbs

### Case Specifications

	<b>W-CASE</b>	<b>S9-CASE</b>
<b>Model:</b>	<b>W-CASE</b>	<b>S9-CASE</b>
<b>Stores:</b>	WalkAbout II, camera and accessories	T-FNS-11
<b>Construction:</b>	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.	Soft padded carry case for the pole.
<b>Size:</b>	21" x 16" x 8"	48" x 8" x 2"
<b>Weight loaded:</b>	18 lbs	5 lbs

### RECOMMENDED OPTIONS

<b>Spare battery</b>	A spare battery allows one battery to be charging while the other one is in use. HIGHLY RECOMMENDED.
<b>D-BAT</b>	Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.
<b>Baton</b>	2ft Baton allows access to confined spaces.

<b>Note 1:</b>	Add a "-P" to the end of the system part number to specify a PAL (European TV standard) system (WA-SPW11-P). Change the system part number prefix "WA-" to "WS-" to specify the WalkAbout Sling (WSH) in place of the Chest Harness (WCH).
----------------	---