



P O R T A B L E  
V I D E O  
S Y S T E M S


# VEHICLE SEARCH SYSTEM DELUXE

PART # WA-VSWD14



**Kit Includes:**

- |  |  |
|--|--|
| <b>A</b> WalkAbout II™ Display (WM-4) with Chest Harness (WCH) | <b>G</b> Battery Charger (WBC-PS1)                   |
| <b>B</b> WalkAbout II Sunshade (SS-WA)                         | <b>H</b> Two (2) NiMH Rechargeable Batteries (BAT-2) |
| <b>C</b> Low Light Color Camera (LLC-1.4)                      | <b>I</b> 2-Foot Baton (B-FNS)                        |
| <b>D</b> Low Light Color Camera (WPC-1.2)                      | <b>J</b> 14-Foot Telescoping Pole (T-FNS-14)         |
| <b>E</b> Wide Angle Color Camera (WPC-3.5)                     | <b>K</b> 6-Foot Rigid Wand for UVIT (RW)             |
| <b>F</b> Under Vehicle Inspection Trolley (UVIT)               | <b>L</b> Carrying Case (V-CASE)                      |

**Notes:** Also available with sling configuration (substitute "WS-" for "WA-")   
Also available without B-FNS baton and LLC-1.4 camera (substitute "-WSW14" for "-VSWD14")





# VEHICLE SEARCH SYSTEM SPECIFICATIONS

WA-VSW14<sup>1</sup> / WA-VSWD14<sup>1</sup>

## WalkAbout II Monitor Specifications

<b>Size:</b>	6.4"W x 4.5"H x 2.2"D (LCD); 4.8"L x 3.4"W x 2.8"H (Base)	<b>Weight:</b>	3.75lbs (with battery)
<b>Construction:</b>	Aluminum case encapsulated in rubber for shock resistance and weatherproofing	<b>Operating temperature range:</b>	-20C to 70C
<b>Display size:</b>	5" diagonal	<b>Resolution:</b>	960 dots x 234 lines
<b>Video format:</b>	Auto switches between NTSC (American) or PAL (European) format		
<b>Batteries:</b>	Internal NiMH, 7.2V, 2.7AH	<b>Discharge time:</b>	2hrs - Camera LEDES off & LCD on
<b>Charger:</b>	NiMH charger. Operates on 12VDC from either power supply or vehicle adapter.	<b>Charge time:</b>	2hrs if fully discharged
<b>LCD Controls:</b>	Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down	<b>Base Controls and indicators:</b>	Main On/OFF push button switch; Camera LED intensity control LED Indicators: PWR ON, LOW BAT, CAM LED
<b>Connections:</b>	1) Camera (pole) receptacle, 2) A/V output receptacle, 3) External DC input receptacle, 7.2-12VDC @ 15W max	<b>Mounting options:</b>	Belt clip onto vest/belt or Chest Harness (supplied)

## Camera Specifications

<b>Model:</b>	<b>WPC-1.2</b>	<b>LLC-1.4</b>	<b>WPC-3.5</b>
<b>Construction:</b>	Submersible enclosure with hard-coated polycarbonate window		Submersible, non conductive enclosure with hard-coated polycarbonate window
<b>Size / weight:</b>	1.2" dia x 2.5" long / .2 lbs	1.4" dia x 2.8" long / .2 lbs	2.5" dia x 2.5" long / .33 lbs
<b>Features:</b>	6 bright white LED illuminated, color camera, 400 lines, .03 lux, 6.0 mm lens, 53° FOV	6 bright white LED illuminated, color camera, 400 lines, .03 lux, 6.0 mm lens, 53° FOV.	45 bright white LED illuminated, color camera, 400 lines, .03 lux, 3.6 mm lens, 92° FOV
<b>Use:</b>	For use on either pole or Baton. (LLC-1.4 is only part of WA-VSWD14)		Wide angle lens for use on UVIT

## Pole Specifications

<b>Model:</b>	<b>UVIT</b>	<b>T-FNS-14</b>	<b>B-FNS</b>
<b>Name:</b>	<b>Under Vehicle Inspection Trolley</b>	<b>Telescoping Pole</b>	<b>Baton</b>
<b>Pole Construction:</b>	2 section telescoping fiberglass detachable handle. Rugged aluminum trolley with 4 wheels on base.	4 section telescoping fiberglass pole with foam grip	Fixed length fiberglass pole with hand grip
<b>Collars:</b>	Rugged, break-proof, easy grip, twist collars for each pole section		None
<b>Articulation:</b>	Rotating handle rotates camera	1ft gooseneck can be flexed to any position	
<b>Collapsed length:</b>	4 ft	4 ft collapsed and folded	1 ft 4in collapsed and folded
<b>Extended length:</b>	6ft 6in handle	14 ft	2 ft
<b>Weight:</b>	6 lbs	5 lbs	1 lb
<b>Use:</b>	Search under vehicles	Search on top of and in cargo compartments of vehicles	Search in confined spaces such as in the passenger compartment. Only part of Deluxe System WA-VSWD14

## Case Specifications

<b>Model:</b>	<b>V-CASE</b>
<b>Construction:</b>	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
<b>Size / weight:</b>	53" x 17" x 6" / 45 lbs (WA-VSW14) / 46 lbs (WA-VSWD14)

<b>Note 1:</b>	Add a "-P" to the end of the system part number to specify a PAL (European TV standard) system (WA-VSW14-P or WA-VSWD14-P). Change the system part number prefix "WA-" to "WS-" to specify the WalkAbout Sling (WSH) in place of the Chest Harness (WCH).
----------------	--